










GENERAL PURPOSE BALL VALVES



FORGED BRASS BALL VALVE - FULL PORT				FORGED BRASS BALL VALVE - FULL PORT				FORGED BRASS 3-WAY BALL VALVE																																																																																																																	
 <p>PIPE Female To Female</p> <table border="1"> <thead> <tr> <th>PART No.</th> <th>Pipe</th> <th>W.O.G.</th> <th>W.S.P.</th> </tr> </thead> <tbody> <tr><td>BV2103-A</td><td>1/8</td><td>600</td><td>150</td></tr> <tr><td>BV2103-B</td><td>1/4</td><td>600</td><td>150</td></tr> <tr><td>BV2103-C</td><td>3/8</td><td>600</td><td>150</td></tr> <tr><td>BV2103-D</td><td>1/2</td><td>600</td><td>150</td></tr> <tr><td>BV2103-E</td><td>3/4</td><td>600</td><td>150</td></tr> <tr><td>BV2103-H</td><td>1</td><td>600</td><td>150</td></tr> <tr><td>BV2103-J</td><td>1-1/4</td><td>600</td><td>150</td></tr> <tr><td>BV2103-K</td><td>1-1/2</td><td>600</td><td>150</td></tr> <tr><td>BV2103-M</td><td>2</td><td>600</td><td>150</td></tr> <tr><td>BV2103-N</td><td>2-1/2</td><td>400</td><td>150</td></tr> <tr><td>BV2103-P</td><td>3</td><td>400</td><td>150</td></tr> </tbody> </table>				PART No.	Pipe	W.O.G.	W.S.P.	BV2103-A	1/8	600	150	BV2103-B	1/4	600	150	BV2103-C	3/8	600	150	BV2103-D	1/2	600	150	BV2103-E	3/4	600	150	BV2103-H	1	600	150	BV2103-J	1-1/4	600	150	BV2103-K	1-1/2	600	150	BV2103-M	2	600	150	BV2103-N	2-1/2	400	150	BV2103-P	3	400	150	 <p>PIPE Female To Female</p> <p><i>With Locking Handle</i></p> <table border="1"> <thead> <tr> <th>PART No.</th> <th>Pipe</th> <th>W.O.G.</th> <th>W.S.P.</th> </tr> </thead> <tbody> <tr><td>BV2103-B-LH</td><td>1/4</td><td>600</td><td>150</td></tr> <tr><td>BV2103-C-LH</td><td>3/8</td><td>600</td><td>150</td></tr> <tr><td>BV2103-D-LH</td><td>1/2</td><td>600</td><td>150</td></tr> <tr><td>BV2103-E-LH</td><td>3/4</td><td>600</td><td>150</td></tr> <tr><td>BV2103-H-LH</td><td>1</td><td>600</td><td>150</td></tr> <tr><td>BV2103-J-LH</td><td>1-1/4</td><td>600</td><td>150</td></tr> <tr><td>BV2103-K-LH</td><td>1-1/2</td><td>600</td><td>150</td></tr> <tr><td>BV2103-M-LH</td><td>2</td><td>600</td><td>150</td></tr> </tbody> </table>				PART No.	Pipe	W.O.G.	W.S.P.	BV2103-B-LH	1/4	600	150	BV2103-C-LH	3/8	600	150	BV2103-D-LH	1/2	600	150	BV2103-E-LH	3/4	600	150	BV2103-H-LH	1	600	150	BV2103-J-LH	1-1/4	600	150	BV2103-K-LH	1-1/2	600	150	BV2103-M-LH	2	600	150	 <p>PIPE Female Ends 3 - Way</p> <table border="1"> <thead> <tr> <th>PART No.</th> <th>Pipe</th> <th>W.O.G.</th> </tr> </thead> <tbody> <tr><td>BV2101-B</td><td>1/4</td><td>400</td></tr> <tr><td>BV2101-C</td><td>3/8</td><td>400</td></tr> <tr><td>BV2101-D</td><td>1/2</td><td>400</td></tr> <tr><td>BV2101-E</td><td>3/4</td><td>400</td></tr> <tr><td>BV2101-H</td><td>1</td><td>400</td></tr> <tr><td>BV2101-J</td><td>1-1/4</td><td>400</td></tr> <tr><td>BV2101-K</td><td>1-1/2</td><td>400</td></tr> <tr><td>BV2101-M</td><td>2</td><td>400</td></tr> </tbody> </table>			PART No.	Pipe	W.O.G.	BV2101-B	1/4	400	BV2101-C	3/8	400	BV2101-D	1/2	400	BV2101-E	3/4	400	BV2101-H	1	400	BV2101-J	1-1/4	400	BV2101-K	1-1/2	400	BV2101-M	2	400
PART No.	Pipe	W.O.G.	W.S.P.																																																																																																																						
BV2103-A	1/8	600	150																																																																																																																						
BV2103-B	1/4	600	150																																																																																																																						
BV2103-C	3/8	600	150																																																																																																																						
BV2103-D	1/2	600	150																																																																																																																						
BV2103-E	3/4	600	150																																																																																																																						
BV2103-H	1	600	150																																																																																																																						
BV2103-J	1-1/4	600	150																																																																																																																						
BV2103-K	1-1/2	600	150																																																																																																																						
BV2103-M	2	600	150																																																																																																																						
BV2103-N	2-1/2	400	150																																																																																																																						
BV2103-P	3	400	150																																																																																																																						
PART No.	Pipe	W.O.G.	W.S.P.																																																																																																																						
BV2103-B-LH	1/4	600	150																																																																																																																						
BV2103-C-LH	3/8	600	150																																																																																																																						
BV2103-D-LH	1/2	600	150																																																																																																																						
BV2103-E-LH	3/4	600	150																																																																																																																						
BV2103-H-LH	1	600	150																																																																																																																						
BV2103-J-LH	1-1/4	600	150																																																																																																																						
BV2103-K-LH	1-1/2	600	150																																																																																																																						
BV2103-M-LH	2	600	150																																																																																																																						
PART No.	Pipe	W.O.G.																																																																																																																							
BV2101-B	1/4	400																																																																																																																							
BV2101-C	3/8	400																																																																																																																							
BV2101-D	1/2	400																																																																																																																							
BV2101-E	3/4	400																																																																																																																							
BV2101-H	1	400																																																																																																																							
BV2101-J	1-1/4	400																																																																																																																							
BV2101-K	1-1/2	400																																																																																																																							
BV2101-M	2	400																																																																																																																							
BRASS BALL VALVE - FULL PORT				BRASS BALL VALVE - FULL PORT STAINLESS STEEL HANDLE				FORGED BRASS 3-WAY BALL VALVE																																																																																																																	
 <p>PIPE Female To Female</p> <table border="1"> <thead> <tr> <th>PART No.</th> <th>Pipe</th> <th>W.O.G.</th> </tr> </thead> <tbody> <tr><td>BV4103-B</td><td>1/4</td><td>600</td></tr> <tr><td>BV4103-C</td><td>3/8</td><td>600</td></tr> <tr><td>BV4103-D</td><td>1/2</td><td>600</td></tr> <tr><td>BV4103-E</td><td>3/4</td><td>600</td></tr> <tr><td>BV4103-H</td><td>1</td><td>600</td></tr> <tr><td>BV4103-J</td><td>1-1/4</td><td>600</td></tr> <tr><td>BV4103-K</td><td>1-1/2</td><td>600</td></tr> <tr><td>BV4103-M</td><td>2</td><td>600</td></tr> <tr><td>BV4103-N *</td><td>2-1/2</td><td>400</td></tr> <tr><td>BV4103-P *</td><td>3</td><td>400</td></tr> <tr><td>BV4103-S *</td><td>4</td><td>400</td></tr> </tbody> </table> <p><i>* Complete with Stainless Steel Handles.</i></p>				PART No.	Pipe	W.O.G.	BV4103-B	1/4	600	BV4103-C	3/8	600	BV4103-D	1/2	600	BV4103-E	3/4	600	BV4103-H	1	600	BV4103-J	1-1/4	600	BV4103-K	1-1/2	600	BV4103-M	2	600	BV4103-N *	2-1/2	400	BV4103-P *	3	400	BV4103-S *	4	400	 <p>PIPE Female To Female</p> <table border="1"> <thead> <tr> <th>PART No.</th> <th>Pipe</th> <th>W.O.G.</th> </tr> </thead> <tbody> <tr><td>BV4103-B-SSH</td><td>1/4</td><td>600</td></tr> <tr><td>BV4103-C-SSH</td><td>3/8</td><td>600</td></tr> <tr><td>BV4103-D-SSH</td><td>1/2</td><td>600</td></tr> <tr><td>BV4103-E-SSH</td><td>3/4</td><td>600</td></tr> <tr><td>BV4103-H-SSH</td><td>1</td><td>600</td></tr> <tr><td>BV4103-J-SSH</td><td>1-1/4</td><td>600</td></tr> <tr><td>BV4103-K-SSH</td><td>1-1/2</td><td>600</td></tr> <tr><td>BV4103-M-SSH</td><td>2</td><td>600</td></tr> </tbody> </table>				PART No.	Pipe	W.O.G.	BV4103-B-SSH	1/4	600	BV4103-C-SSH	3/8	600	BV4103-D-SSH	1/2	600	BV4103-E-SSH	3/4	600	BV4103-H-SSH	1	600	BV4103-J-SSH	1-1/4	600	BV4103-K-SSH	1-1/2	600	BV4103-M-SSH	2	600	 <p>PIPE Female Ends 3 - Way</p> <p>PRESSURE RATING: Bottom Port as inlet 500 P.S.I. Side Port as inlet 100 P.S.I.</p> <table border="1"> <thead> <tr> <th>PART No.</th> <th>Pipe</th> </tr> </thead> <tbody> <tr><td>BV2101T-B</td><td>1/4</td></tr> <tr><td>BV2101T-C</td><td>3/8</td></tr> <tr><td>BV2101T-D</td><td>1/2</td></tr> </tbody> </table>			PART No.	Pipe	BV2101T-B	1/4	BV2101T-C	3/8	BV2101T-D	1/2																																								
PART No.	Pipe	W.O.G.																																																																																																																							
BV4103-B	1/4	600																																																																																																																							
BV4103-C	3/8	600																																																																																																																							
BV4103-D	1/2	600																																																																																																																							
BV4103-E	3/4	600																																																																																																																							
BV4103-H	1	600																																																																																																																							
BV4103-J	1-1/4	600																																																																																																																							
BV4103-K	1-1/2	600																																																																																																																							
BV4103-M	2	600																																																																																																																							
BV4103-N *	2-1/2	400																																																																																																																							
BV4103-P *	3	400																																																																																																																							
BV4103-S *	4	400																																																																																																																							
PART No.	Pipe	W.O.G.																																																																																																																							
BV4103-B-SSH	1/4	600																																																																																																																							
BV4103-C-SSH	3/8	600																																																																																																																							
BV4103-D-SSH	1/2	600																																																																																																																							
BV4103-E-SSH	3/4	600																																																																																																																							
BV4103-H-SSH	1	600																																																																																																																							
BV4103-J-SSH	1-1/4	600																																																																																																																							
BV4103-K-SSH	1-1/2	600																																																																																																																							
BV4103-M-SSH	2	600																																																																																																																							
PART No.	Pipe																																																																																																																								
BV2101T-B	1/4																																																																																																																								
BV2101T-C	3/8																																																																																																																								
BV2101T-D	1/2																																																																																																																								
BRASS BALL VALVE - FULL PORT				SAFETY EXHAUST BALL VALVE				SAFETY EXHAUST BALL VALVE																																																																																																																	
 <p>SOLDER Female To Female</p> <table border="1"> <thead> <tr> <th>PART No.</th> <th>Type K Size</th> <th>W.O.G.</th> </tr> </thead> <tbody> <tr><td>BVC4103-10</td><td>1/2</td><td>600</td></tr> <tr><td>BVC4103-14</td><td>3/4</td><td>600</td></tr> <tr><td>BVC4103-18</td><td>1</td><td>600</td></tr> <tr><td>BVC4103-22</td><td>1-1/4</td><td>600</td></tr> <tr><td>BVC4103-26</td><td>1-1/2</td><td>600</td></tr> <tr><td>BVC4103-34</td><td>2</td><td>600</td></tr> </tbody> </table> <p>SOLDERING TEMPERATURES NOT TO EXCEED 400 degrees F.</p>				PART No.	Type K Size	W.O.G.	BVC4103-10	1/2	600	BVC4103-14	3/4	600	BVC4103-18	1	600	BVC4103-22	1-1/4	600	BVC4103-26	1-1/2	600	BVC4103-34	2	600	 <p>PIPE Female To Female</p> <table border="1"> <thead> <tr> <th>PART No.</th> <th>Pipe</th> </tr> </thead> <tbody> <tr><td>BVSE2103-B</td><td>1/4</td></tr> <tr><td>BVSE2103-C</td><td>3/8</td></tr> <tr><td>BVSE2103-D</td><td>1/2</td></tr> <tr><td>BVSE2103-E</td><td>3/4</td></tr> </tbody> </table> <p><i>THIS VALVE IS DESIGNED TO EXHAUST DOWNSTREAM AIR IN THE CLOSED POSITION.</i></p>				PART No.	Pipe	BVSE2103-B	1/4	BVSE2103-C	3/8	BVSE2103-D	1/2	BVSE2103-E	3/4	 <p>PIPE Female To Female</p> <p><i>With Locking Handle</i></p> <table border="1"> <thead> <tr> <th>PART No.</th> <th>Pipe</th> </tr> </thead> <tbody> <tr><td>BVSE2103-B-LH</td><td>1/4</td></tr> <tr><td>BVSE2103-C-LH</td><td>3/8</td></tr> <tr><td>BVSE2103-D-LH</td><td>1/2</td></tr> <tr><td>BVSE2103-E-LH</td><td>3/4</td></tr> </tbody> </table> <p><i>THIS VALVE IS DESIGNED TO EXHAUST DOWNSTREAM AIR IN THE CLOSED POSITION.</i></p>			PART No.	Pipe	BVSE2103-B-LH	1/4	BVSE2103-C-LH	3/8	BVSE2103-D-LH	1/2	BVSE2103-E-LH	3/4																																																																						
PART No.	Type K Size	W.O.G.																																																																																																																							
BVC4103-10	1/2	600																																																																																																																							
BVC4103-14	3/4	600																																																																																																																							
BVC4103-18	1	600																																																																																																																							
BVC4103-22	1-1/4	600																																																																																																																							
BVC4103-26	1-1/2	600																																																																																																																							
BVC4103-34	2	600																																																																																																																							
PART No.	Pipe																																																																																																																								
BVSE2103-B	1/4																																																																																																																								
BVSE2103-C	3/8																																																																																																																								
BVSE2103-D	1/2																																																																																																																								
BVSE2103-E	3/4																																																																																																																								
PART No.	Pipe																																																																																																																								
BVSE2103-B-LH	1/4																																																																																																																								
BVSE2103-C-LH	3/8																																																																																																																								
BVSE2103-D-LH	1/2																																																																																																																								
BVSE2103-E-LH	3/4																																																																																																																								
W.O.G. = WATER, OIL AND GAS W.S.P. = WORKING STEAM PRESSURE																																																																																																																									

F1



C.S.A. CERTIFIED FORGED BRASS BALL VALVES FOR NATURAL AND PROPANE GAS (VAPOUR)

FOR INDOOR / OUTDOOR APPLICATIONS



**PIPE
Female
To
Female**

PART No.	Pipe
BV2103-B-CGA	1/4
BV2103-C-CGA	3/8
BV2103-D-CGA	1/2
BV2103-E-CGA	3/4
BV2103-H-CGA	1
BV2103-J-CGA	1-1/4
BV2103-K-CGA	1-1/2
BV2103-M-CGA	2



**C.S.A. certified to C.G.A. (3.16) rated for 125 P.S.I.
Temperature:** -40°F to +150°F, -40°C to +65°C.



**PIPE
Female
To
Female**

PART No.	Pipe
BV5221-C	3/8
BV5221-D	1/2
BV5221-E	3/4



**C.S.A. certified to 5 P.S.I.
Temperature:** -40°F to +125°F, -40°C to +52°C.



**PIPE
Female
To
Female**

PART No.	Pipe
BV5223-D	1/2
BV5223-E	3/4



**C.S.A. certified to 5 P.S.I.
Temperature:** -40°F to +125°F, -40°C to +52°C.



**FLARE
Tube
To
Tube**

PART No.	Tube	Temperature
BV5042-6	3/8	
BV5042-8	1/2	
BV5042-10	5/8	



**C.S.A. certified to 5 P.S.I. from the appliance to the meter.
Temperature:** -40°F to +125°F, -40°C to +52°C.



**FLARE
Tube
To
Female Pipe**

PART No.	Tube	Pipe
BV5046-6D	3/8	1/2
BV5046-8D	1/2	1/2



**C.S.A. certified to 5 P.S.I. from the appliance to the meter.
Temperature:** -40°F to +125°F, -40°C to +52°C.



**FLARE
Tube
To
Male Pipe**

PART No.	Tube	Pipe
BV5048-6D	3/8	1/2
BV5048-8D	1/2	1/2



**C.S.A. certified to 5 P.S.I. from the appliance to the meter.
Temperature:** -40°F to +125°F, -40°C to +52°C.



**PIPE
Female
To
Female**

PART No.	Pipe
BVT5103-B	1/4
BVT5103-C	3/8
BVT5103-D	1/2
BVT5103-E	3/4
BVT5103-H	1



**C.S.A. certified to 1/2 P.S.I. from the appliance to the meter.
Temperature:** -40°F to +230°F, -40°C to +110°C.

**C.S.A. certified to 5 P.S.I.
Temperature:** +32°F to +125°F, 0°C to +52°C.

NOTE: Style of handle varies with pipe size.

CERTIFICATIONS CAN EXPIRE. THEY SHOULD BE CONFIRMED WITH THE APPROVING AGENCIES.

LIQUID / VAPOUR LP GAS SHUT-OFF VALVES

Ideally suited for use on bobtails and in bulk plant systems storing and handling LP-Gas in either liquid or gaseous phase. Large port sizes for maximum flow capacity.



**PIPE
Female
To
Female**

PART No.	Pipe
BV351TKL-B	1/4
BV351TKL-C	3/8
BV351TKL-D	1/2
BV351TKL-E **	3/4
BV351TKL-H **	1
BV351TKL-J	1-1/4
BV351TKL-K	1-1/2
BV351TKL-M	2



UL Listed - Standard YSTD to 600 PSIG (-20°F to +100°F)
 ** CSA Certified to CGA 3.16 to 125 PSIG (-40°F to +125°F)

MANOMETER VALVES



**PIPE
Female
To
Female**

PART No.	Pipe
BVTM5103-B	1/4
BVTM5103-C	3/8
BVTM5103-D	1/2
BVTM5103-E	3/4
BVTM5103-H	1



C.S.A. certified to 1/2 P.S.I. from the appliance to the meter.
Temperature:-40°F to +230°F, -40°C to +110°C



**FLARE
Tube
To
Tube**

PART No.	Tube
BVTM5042-6	3/8
BVTM5042-8	1/2
BVTM5042-10	5/8



C.S.A. certified to 1/2 P.S.I. from the appliance to the meter.
Temperature:-40°F to +230°F, -40°C to +110°C

MINIATURE BALL VALVES

- Up to 600 P.S.I. Working Pressure.
- Non-adjusting O-Ring stem seal design never needs tightening.
- Long life nickel plated brass ball.
- Instantaneous on-off operation.
- Designed for use with water, oil and air pressure systems.
- ASTM B-16 corrosion resistant brass body.
- Highly inert teflon® seats.
- Blow-out proof stem for safety.
- Quarter turn handle design.



**PIPE
Female
To
Female**

PART No.	Pipe	Pipe
BV3103-A	1/8	1/8
BV3103-B	1/4	1/4



**PIPE
Female
To
Male**

PART No.	Pipe	Pipe
BV3120-A	1/8	1/8
BV3120-B	1/4	1/4





**HOSE
TO
PIPE**

PART No.	Hose	Pipe
BV3125-4B	1/4	1/4
BV3125-6B	3/8	1/4



CERTIFICATIONS CAN EXPIRE. THEY SHOULD BE CONFIRMED WITH THE APPROVING AGENCIES.



CARBON AND STAINLESS STEEL BALL VALVES

1 - PIECE DESIGN, STANDARD PORT			2 - PIECE DESIGN, FULL PORT		
STAINLESS STEEL			STAINLESS STEEL		
					
PART No.	W.O.G.	Female Pipe	PART No.	W.O.G.	Female Pipe
BVSS2003-B-800	800	1/4	BVSS2003-B-1000	1000	1/4
BVSS2003-C-800	800	3/8	BVSS2003-C-1000	1000	3/8
BVSS2003-D-800	800	1/2	BVSS2003-D-1000	1000	1/2
BVSS2003-E-800	800	3/4	BVSS2003-E-1000	1000	3/4
BVSS2003-H-800	800	1	BVSS2003-H-1000	1000	1
BVSS2003-J-800	800	1-1/4	BVSS2003-J-1000	1000	1-1/4
BVSS2003-K-800	800	1-1/2	BVSS2003-K-1000	1000	1-1/2
BVSS2003-M-800	800	2	BVSS2003-M-1000	1000	2

F4

1 - PIECE BAR STOCK DESIGN, STANDARD PORT					
CARBON STEEL			STAINLESS STEEL		
					
PART No.	W.O.G.	Female Pipe	PART No.	W.O.G.	Female Pipe
BVCS2103-B	2000	1/4	BVSS2103-B	2000	1/4
BVCS2103-C	2000	3/8	BVSS2103-C	2000	3/8
BVCS2103-D	2000	1/2	BVSS2103-D	2000	1/2
BVCS2103-E	2000	3/4	BVSS2103-E	2000	3/4
BVCS2103-H	2000	1	BVSS2103-H	2000	1
BVCS2103-J	2000	1-1/4	BVSS2103-J	2000	1-1/4
BVCS2103-K	2000	1-1/2	BVSS2103-K	2000	1-1/2
BVCS2103-M	2000	2	BVSS2103-M	2000	2

2 - PIECE DESIGN, FULL PORT

CARBON STEEL



PART No.	W.O.G.	Female Pipe
BVCS2203-B	2000	1/4
BVCS2203-C	2000	3/8
BVCS2203-D	2000	1/2
BVCS2203-E	2000	3/4
BVCS2203-H	2000	1
BVCS2203-J	1500	1-1/4
BVCS2203-K	1500	1-1/2
BVCS2203-M	1500	2

STAINLESS STEEL



PART No.	W.O.G.	Female Pipe
BVSS2203-B	2000	1/4
BVSS2203-C	2000	3/8
BVSS2203-D	2000	1/2
BVSS2203-E	2000	3/4
BVSS2203-H	2000	1
BVSS2203-J	1500	1-1/4
BVSS2203-K	1500	1-1/2
BVSS2203-M	1500	2

2 - PIECE DESIGN, MEDIUM PRESSURE, FULL PORT

CARBON STEEL



PART No.	W.O.G.	Female Pipe
BVCS2303-B	3000	1/4
BVCS2303-C	3000	3/8
BVCS2303-D	3000	1/2
BVCS2303-E	3000	3/4
BVCS2303-H	3000	1

STAINLESS STEEL



PART No.	W.O.G.	Female Pipe
BVSS2403-B	5880	1/4
BVSS2403-C	5880	3/8
BVSS2403-D	5880	1/2
BVSS2403-E	5880	3/4
BVSS2403-H	5880	1

3 - PIECE DESIGN, HIGH PRESSURE

CARBON STEEL - NPTF PORTS



PART No.	W.O.G.	Female Pipe	Port Style
BVCS2403-B	7250	1/4	Full
BVCS2403-C	7250	3/8	Full
BVCS2403-D	7250	1/2	Full
BVCS2403-E	5075	3/4	Full
BVCS2403-H	5075	1	Full
BVCS2403-J	5075	1-1/4	Standard
BVCS2403-K	5075	1-1/2	Standard
BVCS2403-M	6174	2	Standard

CARBON STEEL - ORB PORTS



PART No.	W.O.G.	Female O-Ring	Port Style
BVCS2434-4	7250	7/16 - 20	Full
BVCS2434-6	7250	9/16 - 18	Full
BVCS2434-8	7250	3/4 - 16	Full
BVCS2434-12	5075	1-1/16 - 12	Full
BVCS2434-16	5075	1-5/16 - 12	Full

* OTHER CONFIGURATIONS AVAILABLE UPON REQUEST

* ALSO AVAILABLE IN S.A.E. THREADS

F5



NEEDLE VALVES

(FOR WORKING PRESSURE UP TO 150 P.S.I.)



**FLARE
Tube
To
Tube**

PART No.	Tube
3042-4	1/4
3042-6	3/8



**FLARE
ELBOW
Tube
To
Male Pipe**

PART No.	Tube	Pipe
3049-4A	1/4	1/8



**COMPRESSION
Tube
To
Tube**

PART No.	Tube
3062-4	1/4
3062-5	5/16
3062-6	3/8



**COMPRESSION
Tube
To
Male Pipe**

PART No.	Tube	Pipe
3068-4A	1/4	1/8
3068-4B	1/4	1/4
3068-6B	3/8	1/4



**COMPRESSION
Tube
To
Male Pipe**

PART No.	Tube	Pipe
3069-4A	1/4	1/8
3069-4B	1/4	1/4
3069-6B	3/8	1/4



**PIPE
Female
To
Female**

Part No.	Pipe
3103-A	1/8
3103-B	1/4



**PIPE
Female
To
Male**

Part No.	Pipe
3120-A	1/8
3120-B	1/4



**PIPE
Male
To
Male**

Part No.	Pipe
3122-A	1/8
3122-B	1/4



**COMPRESSION
Poly Tube
To
Poly Tube**

PART No.	Tube
3462-4	1/4
3462-5	5/16
3462-6	3/8



**COMPRESSION
Poly Tube
To
Male Pipe**

PART No.	Tube	Pipe
3469-4A	1/4	1/8
3469-4B	1/4	1/4



**HUMIDIFIER
VALVE
Tube
To
Male Pipe**

PART No.	Tube	Pipe
3069-4T	1/4	1/8

F6

NEEDLE VALVE ASSEMBLIES



NEEDLE VALVE ASSEMBLY

Complete With Brass Forged Clamp

PART No.	Description
S3069-4	1/4 O.D. Assembly
S3069-WT	Brass Clamp Only



NEEDLE VALVE ASSEMBLY
Complete With Steel Clamp (Zinc Plated)

PART No.	Description
S3069-4S	1/4 O.D. Assembly
*S3069-ST-4	Self Tapping Assembly
S3069-PC	Steel Clamp Only
S3069-PCW	Sealing Washer

* Packaged complete with insert, sleeve and instructions.

BRASS PRECISION NEEDLE VALVES C.S.A. CERTIFIED FOR L/P GAS TO 350 P.S.I.

These instrumentation valves have knurled brass hand wheels, and are for use with air, LP gases (such as torch applications) and liquids. Each valve is pressure tested at the factory. The valve body is machined from brass bar stock. The stem is stainless steel with a fine thread for controlling flow. O-ring packing assures leak proof trouble free service.



PIPE
Female
To
Male

PART No.	Flow	Pipe
850-A	→	1/8
850-B	→	1/4
850-BRF (REVERSE FLOW)	←	1/4



PIPE
Female
To
Female

PART No.	Pipe
852-A	1/8
852-B	1/4



PIPE
Male
To
Male

PART No.	Pipe
851-A	1/8
851-B	1/4



WELDING
STANDARD
To
Male Pipe

PART No.	Pipe	Flow	Welding Thread
853-L	1/4	→	9/16-18 L.H.
853-R	1/4	→	9/16-18 R.H.
854-L (REVERSE FLOW)	1/4	←	9/16-18 L.H.

C.S.A. CERTIFIED FOR L/P GAS TO 350 P.S.I. MAXIMUM. TEMPERATURE: -40°F to +130°F, -40°C to +54°C
CERTIFICATIONS CAN EXPIRE. THEY SHOULD BE CONFIRMED WITH THE APPROVING AGENCIES.



UTILITY VALVES

GATE VALVES



FEMALE PIPE

PART No.	Pipe	W.O.G.
217-B	1/4	200
217-C	3/8	200
217-D	1/2	200
217-E	3/4	200
217-H	1	200
217-J	1-1/4	200
217-K	1-1/2	200
217-M	2	200
217-N	2-1/2	200
217-P	3	200
217-S	4	200

ANGLE VALVES



Forged Body FLARE TO MALE PIPE

PART No.	Tube	Pipe	P.S.I.
1049-6B	3/8	1/4	200
1049-6C	3/8	3/8	200
1049-6D	3/8	1/2	200
1049-8C	1/2	3/8	200
1049-10D	5/8	1/2	200

SELECTOR VALVES WITH CLICK



**THREE WAY
SHUT-OFF**
With Mounting Bracket
Flow Either Of
Two Side Ports
To Center Port,
All Ports Female Pipe

PART No.	Pipe	Stem Length	P.S.I.
2101-B	1/4	1-3/8"	30
2101-BL	1/4	2-7/8"	30
2101-C	3/8	1-3/8"	30

OPERATING TEMPERATURE: -40° F to +180°F, -40°C to +82°C



**FOUR WAY
SHUT-OFF**
With Mounting Bracket
Flow Either Of
Three Side Ports
To Bottom Port,
All Ports Female Pipe

PART No.	Pipe	Stem Length	P.S.I.
2102-B	1/4	1-3/8"	30
2102-C	3/8	1-3/8"	30

OPERATING TEMPERATURE: -40° F to +180°F, -40°C to +82°C



Forged Body HOSE TO MALE PIPE

PART No.	Hose I.D.	Pipe	P.S.I.
1139-6C	3/8	3/8	200
1139-8C	1/2	3/8	200
1139-10C	5/8	3/8	200
1139-10D	5/8	1/2	200
1139-12C	3/4	3/8	200
1139-12D	3/4	1/2	200



Forged Body Heater Valve HOSE TO MALE PIPE

PART No.	Hose I.D.	Pipe	P.S.I.
HV1139-10C	5/8	3/8	200



Forged Body MALE PIPE TO FEMALE PIPE

PART No.	Male Pipe	Female Pipe	P.S.I.
1115-CC	3/8	3/8	200
1115-DC	1/2	3/8	200



Forged Body FLARE TO MALE PIPE

PART No.	Tube	Pipe	P.S.I.
1054-6D	3/8	1/2	200
1054-6E	3/8	3/4	200

F8

OIL TANK VALVES



**MALE PIPE
TO
MALE PIPE**

PART No. 1122-DC
Pipe 1/2 **Pipe** 3/8 **W.O.G.** 200



**MALE FLARE
TO
MALE PIPE**

PART No. 1048-6D
Tube 3/8 **Pipe** 1/2 **W.O.G.** 200
(Complete with flare nut 40-6)



**1/4 TURN
BALL VALVE
MALE PIPE
TO
MALE PIPE**

PART No. BV1122-DC
Pipe 1/2 **Pipe** 3/8 **W.O.G.** 200



**1/4 TURN
BALL VALVE
MALE FLARE
TO
MALE PIPE**

PART No. BV1048-6D
Tube 3/8 **Pipe** 1/2 **W.O.G.** 200
(Complete with flare nut 40-6)



**1/4 TURN
90° BALL VALVE
MALE PIPE
TO
MALE PIPE**

CSA Certified to 200 WOG
Temperature: -40°F to +149°F
-40°C to +65°C

PART No. BV1199-DC
Pipe 1/2 **Pipe** 3/8 **W.O.G.** 200



**1/4 TURN
90° BALL VALVE
MALE FLARE TO
MALE PIPE**

PART No. BV1049-6D **Tube** 3/8 **Pipe** 1/2 **W.O.G.** 200
BV1049-8D 1/2 1/2 200
(Complete with forged flare nut)

WATER THREAD VALVES



**WATER HOSE
TO
MALE PIPE**

PART No. 224-D *
224-E **Pipe** 1/2
3/4

* I.D. OF MALE PIPE WILL ACCOMMODATE
1/2 TYPE K COPPER TUBE FOR SOLDERING



**WATER HOSE
TO
MALE PIPE**

PART No. 225-D * **Pipe** 1/2

* I.D. OF MALE PIPE WILL ACCOMMODATE
1/2 TYPE K COPPER TUBE FOR SOLDERING

COMPRESSION BALL VALVE



**FORGED BODY
TUBE TO
TUBE**

PART No. BV2062-10 **Type K Size** 1/2
BV2062-14 3/4
BV2062-18 1

OIL & MOLASSES GATE VALVE



MALE PIPE

PART No. MGV-E **Pipe** 3/4
MGV-H 1
MGV-J 1-1/4
MGV-K 1-1/2
MGV-M 2
MGV-P 3
MGV-S 4

DRUM AND BARREL FAUCETS

**NOT AFFECTED
BY WEATHER**



SELF-CLOSING NYLON SEAT

PART No. G261 **Pipe** 3/4

FOR USE WITH:

- All Petroleum Products
- Degreasing Hydrocarbon Liquids
- Alcohol • Auto Anti-Freeze
- Lacquers • Varnishes • Thinners

NOTE:

Not For Use With Trichlorethylene And Other Chlorinated Products
Or Detergents And Water Solution Chemicals.



HEAVY DUTY

PART No. 262-E **Pipe** 3/4

F9



SHUT-OFF COCKS

BRASS SPRING BOTTOM SHUT-OFF COCKS

(Not Recommended For Use With Liquids)



**FLARE
Tube
To
Tube**

PART No.	Tube	P.S.I.
2042-4	1/4	30
2042-6	3/8	30
2042-8	1/2	30

TEMPERATURE: -40°F to +250°F
-40°C to +121°C



**COMPRESSION
Tube
To
Male Pipe**

PART No.	Tube	Pipe	P.S.I.
2068-4B	1/4	1/4	30

TEMPERATURE: -40°F to +250°F
-40°C to +121°C



**PIPE
Male
To
Male**

PART No.	Pipe	P.S.I.
2122-A	1/8	30
2122-B	1/4	30
2122-C	3/8	30

TEMPERATURE: -40°F to +250°F
-40°C to +121°C



**FLARE
Tube
To
Male Pipe**

PART No.	Tube	Pipe	P.S.I.
2048-4A	1/4	1/8	30
2048-4B	1/4	1/4	30
2048-5B	5/16	1/4	30
2048-6B	3/8	1/4	30
2048-6C	3/8	3/8	30

TEMPERATURE: -40°F to +250°F
-40°C to +121°C



**PIPE
Female
To
Female**

PART No.	Pipe	P.S.I.
2103-A	1/8	30
2103-B	1/4	30
2103-C	3/8	30

TEMPERATURE: -40°F to +250°F
-40°C to +121°C

SHUT-OFF COCKS FOR POLY TUBE



**COMPRESSION
Poly Tube
To
Poly Tube**

PART No.	Tube	P.S.I.
2462-4	1/4	30
2462-5	5/16	30
2462-6	3/8	30
2462-8	1/2	30

WORKING PRESSURE TO 30 P.S.I.
AT MODERATE TEMPERATURES.



**COMPRESSION
Tube
To
Tube**

PART No.	Tube	P.S.I.
2062-4	1/4	30
2062-5	5/16	30
2062-6	3/8	30
2062-8	1/2	30

TEMPERATURE: -40°F to +250°F
-40°C to +121°C



**PIPE
Female
To
Male**

PART No.	Pipe	P.S.I.
2120-A	1/8	30
2120-B	1/4	30
2120-C	3/8	30

TEMPERATURE: -40°F to +250°F
-40°C to +121°C

BRASS CLOSED BOTTOM SHUT-OFF COCKS



**PIPE
Female
To
Female**

PART No.	Pipe	P.S.I.
5103-A	1/8	30
5103-B	1/4	30
5103-C	3/8	30

TEMPERATURE: -40°F to +250°F
-40°C to +121°C



**PIPE
Female
To
Male**

PART No.	Pipe	P.S.I.
5120-A	1/8	30
5120-B	1/4	30
5120-C	3/8	30

TEMPERATURE: -40°F to +250°F
-40°C to +121°C



**PIPE
Male
To
Male**

PART No.	Pipe	P.S.I.
5122-A	1/8	30
5122-B	1/4	30
5122-C	3/8	30

TEMPERATURE: -40°F to +250°F
-40°C to +121°C

F10

SHUT-OFF COCKS

HEX SHOULDER - TEE HANDLE



**DOUBLE FEMALE
Hex Shoulder
Tee Handle**

PART No.	Pipe	P.S.I.
6103-A	1/8	100
6103-B	1/4	100

TEMPERATURE: 0°F to +180°F
-18°C to +82°C



**DOUBLE MALE
Hex Shoulder
Tee Handle**

PART No.	Pipe	P.S.I.
6122-A	1/8	100
6122-B	1/4	100

TEMPERATURE: 0°F to +180°F
-18°C to +82°C



**MALE AND
FEMALE
Hex Shoulder
Tee Handle**

PART No.	Pipe	P.S.I.
6120-A	1/8	100
6120-B	1/4	100
6120-C	3/8	100

TEMPERATURE: 0°F to +180°F
-18°C to +82°C



**STRAIGHT DRAIN
Hex Shoulder
Tee Handle**

PART No.	Pipe	P.S.I.
6125-A	1/8	100
6125-B	1/4	100

TEMPERATURE: 0°F to +180°F
-18°C to +82°C

ROUND SHOULDER - TEE HANDLE



**DOUBLE FEMALE
Round Shoulder
Tee Handle**

PART No.	Pipe	P.S.I.
7103-A	1/8	100
7103-B	1/4	100
7103-C	3/8	100

TEMPERATURE: 0°F to +180°F
-18°C to +82°C



**MALE AND
FEMALE
Round Shoulder
Tee Handle**

PART No.	Pipe	P.S.I.
7120-A	1/8	100
7120-B	1/4	100
7120-C	3/8	100

TEMPERATURE: 0°F to +180°F
-18°C to +82°C

HEX SHOULDER - LEVER HANDLE



**DOUBLE FEMALE
Hex Shoulder
Lever Handle**

PART No.	Pipe	P.S.I.
8103-A	1/8	100
8103-B	1/4	100
8103-C	3/8	100

TEMPERATURE: 0°F to +180°F
-18°C to +82°C



**DOUBLE MALE
Hex Shoulder
Lever Handle**

PART No.	Pipe	P.S.I.
8122-B	1/4	100

TEMPERATURE: 0°F to +180°F
-18°C to +82°C



**MALE AND
FEMALE
Hex Shoulder
Lever Handle**

PART No.	Pipe	P.S.I.
8120-A	1/8	100
8120-B	1/4	100
8120-C	3/8	100

TEMPERATURE: 0°F to +180°F
-18°C to +82°C



**STRAIGHT DRAIN
Hex Shoulder
Lever Handle**

PART No.	Pipe	P.S.I.
8125-A	1/8	100
8125-B	1/4	100

TEMPERATURE: 0°F to +180°F
-18°C to +82°C

FAIRVIEW AIR COCKS ARE NOT DESIGNED FOR USE WITH STEAM OR LIQUID.

F11



DRAIN COCKS AND VALVES



BACK SEATING TYPE WITH EXTENSION OUTLET

PART No.	Pipe	Working Pressure (P.S.I.)
239-A	1/8	Designed for Constant Pressure use between 20 and 150 PSI
239-B	1/4	



BACK SEATING TYPE

PART No.	Pipe	Working Pressure (P.S.I.)
240-A	1/8	Designed for Constant Pressure use between 15 and 150 PSI
240-B	1/4	
240-C	3/8	
240-D	1/2	



GROUND KEY PLUG TYPE LEVER HANDLE

PART No.	Pipe	Working Pressure (P.S.I.)
241-A	1/8	30
241-B	1/4	30
241-C	3/8	30
241-D	1/2	30



GROUND KEY PLUG TYPE LEVER HANDLE (Heavy Pattern)

PART No.	Pipe	Working Pressure (P.S.I.)
241HP-B	1/4	150



NEEDLE SEAT ONE PIECE PLUG AND HANDLE

PART No.	Pipe	Working Pressure (P.S.I.)
242-A	1/8	200
242-B	1/4	200
242-C	3/8	200



HEAVY DUTY GROUND KEY PLUG TYPE TEE HANDLE

PART No.	Pipe	Working Pressure (P.S.I.)
T241-B	1/4	150



NEEDLE SEAT

PART No.	Pipe	Working Pressure (P.S.I.)
243-A	1/8	Designed for Constant Pressure use between 15 and 150 PSI
243-B	1/4	
243-C	3/8	



90° ELBOW SHUT-OFF WITH SPOUT

PART No.	Hose I.D.	Pipe	Working Pressure (P.S.I.)
245-A	1/4	1/8	200
245-B	3/8	1/4	200

AIR CHUCKS



Fairview's industrial grade brass ball chucks or Fairview's dual foot filler valve with 1/4" female NPT thread are ideally suited for use on live air lines supplying compressed air.

PART No.	Description
BC-B	Ball Chuck
BC-B-LH	Ball Chuck (Locking handle) **
BC-B-DF	Dual Foot (6-1/2" Overall Length)

BRASS TANK VALVE



AIR TANK VALVE

Fairview's industrial grade brass air tank valve with Male NPT thread for use on compressed air systems.

PART No.	Pipe	Description
BTV-A	1/8"	Complete with Cap
BTV-B	1/4"	Complete with Cap

AIR TANK DRAIN VALVE



PART No.	Pipe	Description
14DV-60B	1/4	60" Cable

BRASS BALL CHECKS



45° S.A.E. FLARE GRAVITY FLOW BALL CHECK CONNECTOR
Tube To Male Pipe

PART No.	Tube	Pipe	Working Pressure (PSI)
43-2A	1/8	1/8	10
43-3A	3/16	1/8	10
43-4A	1/4	1/8	10
43-4B	1/4	1/4	10
43-5A	5/16	1/8	10
43-6B	3/8	1/4	10



COMPRESSION GRAVITY FLOW BALL CHECK CONNECTOR
Tube To Male Pipe

PART No.	Tube	Pipe	Working Pressure (PSI)
63-2A	1/8	1/8	10
63-3A	3/16	1/8	10
63-4A	1/4	1/8	10
63-4B	1/4	1/4	10
63-5A	5/16	1/8	10
63-6B	3/8	1/4	10



GRAVITY FLOW BALL CHECK NIPPLE
Male Pipe

PART No.	Pipe	Working Pressure (PSI)
122BC-A	1/8	10
122BC-B	1/4	10

BRASS CHECK VALVES



COUPLING STYLE CHECK VALVE
Female Pipe

200 P.S.I. non-shock cold water, oil, gas. Forged construction for greater strength. May be installed horizontally or vertically. Less than 1 P.S.I. cracking pressure.

PART No.	Pipe	W.O.G.
103CV-C	3/8	200
103CV-D	1/2	200
103CV-E	3/4	200
103CV-H	1	200
103CV-J	1-1/4	200
103CV-K	1-1/2	200



HIGH PRESSURE COUPLING STYLE CHECK VALVE
Female Pipe

3000 P.S.I. Positive check valve. Stainless steel poppet and spring, viton seal - Less than 1 P.S.I. cracking pressure.

PART No.	Pipe	W.O.G.
103CV-B-3000	1/4	3000
103CV-C-3000	3/8	3000



ONE-WAY CHECK

Precision engineered and manufactured to provide optimum performance for each specified application. All brass construction for years of dependable operation.

PART No.	Pipe	W.O.G.
CV1-C	3/8	120
CV1-D	1/2	120

SWING CHECK VALVES



FEMALE PIPE HEX HEAD

PART No.	Pipe	W.O.G.
293-C	3/8	200
293-D	1/2	200
293-E	3/4	200
293-H	1	200
293-J	1-1/4	200
293-K	1-1/2	200

ALLOWS FLOW IN ONE DIRECTION ONLY



"Y" VALVE FEMALE PIPE HEX HEAD

PART No.	Pipe	W.O.G.
298-C	3/8	200
298-D	1/2	200
298-E	3/4	200
298-H	1	200
298-J	1-1/4	200
298-K	1-1/2	200
298-M	2	200

125 P.S.I. STEAM

ALLOWS FLOW IN ONE DIRECTION ONLY

LIFT TRUCK CHECK CONNECTORS

These quick closing couplings are designed to join the carburetion fuel line to the service valve on motor fuel type applications.

- ACME thread allows quick hand-tight assembly.
- Back checks automatically close when disconnected.
- UL Listed



2088



2089

Fairview PART No.	Inlet Connection	Outlet Connection	Application
2089	3/8" FNPT	1-1/4" M ACME	Service Valve
2088	1-1/4" F ACME	1/4" FNPT	Fuel Line
2089-GASKET	Secondary Gasket Seal		
2089-OR	Primary Gasket Seal		



S.A.E. - J318 GLADHANDS

GH SERIES



Standard

PART No.	Pipe Size	Type	Color Code
GHU	1/2 FPT	Universal	Plain
GHE	1/2 FPT	Emergency	Red
GHS	1/2 FPT	Service	Blue

Order Above Gladhands in quantities of 50 to receive free storage bucket.

GH Series With Umbrella Seal

PART No.	Pipe Size	Type	Color Code
GHU-2	1/2 FPT	Universal	Plain
GHE-2	1/2 FPT	Emergency	Red
GHS-2	1/2 FPT	Service	Blue

SWING AWAY GLADHAND



Rotates Full 180 Degrees
(Coupled With Pacifier)

PART No.	Pipe Size	Type	Color Code
GHU-SW	3/8 FPT	Swing Away	Plain
GHE-SW	3/8 FPT	Swing Away	Red
GHS-SW	3/8 FPT	Swing Away	Blue

REPLACEMENT SEALS



GH-SEAL
STANDARD



GH-SEAL-2
UMBRELLA

PART No.	Type	Color Code
GH-SEAL	Rubber	Black
GH-SEAL-2	Rubber Umbrella Seal	Black
GHE-SEAL	Polyurethane	Red
GHS-SEAL	Polyurethane	Blue

GHM SERIES

Mounting

(Plug Included)



PART No.	Pipe Size	Type	Color Code
GHM-E	3/8 FPT	Emergency	Red
GHM-S	3/8 FPT	Service	Blue

GHV SERIES

Valved



PART No.	Bottom Pipe Size	Back Pipe Size	Type	Color Code
GHV-E	3/8 FPT	1/4 FPT	Emergency	Red
GHV-S	3/8 FPT	—	Service	Blue

GLADHAND DUMMY



PART No.	Description	Color Code
GH-DUMMY	C/W 26" SECURITY CABLE	Plain

GLADHAND GRIPS

PART No.
GH-GRIP



Description
Gladhand Grip
Handles

Sold Only in sets.
(Red and Blue)